


Velia PRO Driver - dimmable 7.5-10W



Technical data

Primary voltage	220-240 VAC 50/60 Hz
Secondary voltage	15-20 Vdc
Secondary amperage	500mA
Min. load	7.5W
Max. load	10W
Efficiency	0,8
Expected lifespan	50,000 hours L90 B10 100,000 hours L70 B50
Dimmable	Yes, trailing edge
Dimensions driver	L: 95 mm, W: 45 mm, H: 30 mm
Dimensions connector box	L: 85 mm, W: 55 mm, H: 30 mm
Possibility of through wiring	Yes, 2 x 3G1,5
Ambient temperature	-20° - +50°
Storage temperature	-20° - +70°
Switching cycles	>25.000
IP-class	IP20
Insulation class	Class II
Fuse	Built-in thermal fuse with auto reset
Environment	Indoor
Material	Plastic
Warranty	5 years
Approvals	CE, SELV



*The drawing is not drawn to scale

Produktinformation

- Built-in thermal fuse with auto reset
- Quick and easy installation
- May only be used with
 Velia PRO item no. 30111012, 30111092, 30111013, 30111093
 Velia PRO Tilt item no. 30112012, 30112032, 30112013, 30112033
 Velia PRO Large Tilt item no. 30132012, 30132013

Prim. 220-240 VAC	500mA	Sec. 15-20 Vdc	7.5 - 10W			

Max. LED driver per circuit breaker

Circuit breaker	R9F12616 (16A)	M9F14213 (13A)	R9F12610 (10A)
Max. number	25	25	25

NB: Always use cables of a type approved for permanent installation according to the current legislation. If the cables are in contact with the lamp cover, use cables with an operating temperature of at least 70° C.

Item no.	EAN no.	Colour	Type
98554013	5704629002494	White	Dimmable driver for Velia PRO